



TH-94 / TH-94SUS

溶接用蝶番

Indent Hinge for Heavy Use



特長

溶接用や重量扉用として配電盤・分電盤・制御盤など比較的大型の機器に適した蝶番です。

用途

配電盤・分電盤・制御盤等

Characteristic


For a welding or heavy weight door, suited for rather large devices such as distribution boards, distribution panels, and control boards.

Application

Distribution boards / Distribution panels / Control boards, etc.

■部品表 Parts List

部番 No.	部品名 Part Name	TH-94		TH-94SUS		数 Quantity
		材質 Material	処理 Finish	材質 Material	処理 Finish	
1	ヒンジピース(A) Hinge Piece(A)	SPHC	—	SUS304	ヘアライン Hairline	1
2	ヒンジピース(B) Hinge Piece(B)				—	1
3	シャフト Pin	SWRM			—	1



寸法・仕様表 Size List & Specification

※扉重量は、蝶番を2個使用した場合の参考値です。 Door weight is the data when using 2 pcs of hinge.

型番 Model No.	A	B	C	D	扉重量 (kg) Door Weight (kg)	自重 (g) Net Weight (g)
TH-94-1	(50)	51	φ6	t2.6	—	79
TH-94SUS-1				t2.5	22	78
TH-94-2	(63)	64	φ7	t2.9	—	140
TH-94SUS-2				t3	28	143
TH-94-3	(74)	76	φ7	t2.9	30	187
TH-94SUS-3				t3	35	184
TH-94-4	(87)	89	φ8	t3	30	270
TH-94SUS-4				—	—	257
TH-94-5	(100)	101.6	φ8	t3	50	426
TH-94SUS-5					60	422
TH-94-6	(118)	127	φ11	t4	55	689
TH-94SUS-6					—	685
TH-94-7	(142)	152	φ12	t4	—	967
TH-94SUS-7					85	962

特注品のご相談承ります Please contact us for custom-made.